

Sterile Millex® syringe filters you can trust.



Research Applications:

Sterile filtration of tissue culture media and additives / Buffers / DMSO / Biological solutions

Membrane	Pore Size (μm)	Diameter (mm)	Process Volume (hold-up)	Housing, sterilization method	Connections (inlet outlet)	10 PK	25 PK	50 PK	100 PK	250 PK
PES Millipore Express® Plus Membrane <small>Fast flow and low binding for cell culture media preparation</small>	0.22	25	100 mL (< 100 μL)	PVC, EO	FLL MLS				SLMPR25SS	
		33	200 mL (< 100 μL)	Modified acrylic, RS	FLL MLS				SLGPR33RS	SLGPR33RB
		50	4-8 L	Acrylic, RS	HB HB	SLGP05010				
	0.45	33	200 mL (< 100 μL)	Modified acrylic, RS	FLL MLS			SLHPR33RS	SLHPR33RB	
PVDF Durapore® Membrane <small>Lowest binding for protein rich solutions</small>	0.22	33	100 mL (< 100 μL)	Modified acrylic, RS	FLL MLS			SLVVR33RS		
		4	1 mL (< 10 μL)	HDPE, EO	FLL Male stepped				SLGV004SL	
		13	10 mL (< 25 μL)	HDPE, EO	FLL MLS				SLGVR13SL	
		25	100 mL (< 100 μL)	PVC, EO	Vented FLL MLS			SLGVVR255F		
	0.45	33	100 mL (< 100 μL)	Modified acrylic, RS	FLL MLS			SLGVR33RS	SLGVR33RB	
		4	1 mL (< 10 μL)	HDPE, EO	FLL Male stepped				SLHV004SL	
		13	10 mL (< 25 μL)	HDPE, EO	FLL MLS			SLHVR13SL		
		33	100 mL (< 100 μL)	Modified acrylic, RS	FLL MLS			SLHVR33RS	SLHVR33RB	
PVDF Durapel™ Membrane <small>Superhydrophobic for air venting and gas filtration</small>	5.0	25	100 mL (< 100 μL)	PVC, EO	FLL MLS				SLSV0R25LS	
MCE MF-Millipore™ Membrane <small>Most referenced general purpose membrane</small>	0.22	25	N/A	PVC, EO	FLL MLL			SLGVSR25US		
Hydrophilic PTFE Membrane <small>Broad chemical compatibility</small>	0.22	25	100 mL (< 100 μL)	HDPE, EO	FLL MLS			SLGSVR255F		
		33	100 mL (< 100 μL)	Modified acrylic, EO	FLL MLS			SLGSR33SS	SLGSR33SB	
		45	100 mL (< 100 μL)	Modified acrylic, EO	FLL MLS			SLHAR33SS	SLHAR33SB	
	0.8	33	100 mL (< 100 μL)	Modified acrylic, EO	FLL MLS			SLAAR33SS	SLAAR33SB	
PTFE Fluoropore™ Membrane <small>Hydrophobic for gas and alcohol filtration</small>	0.2	13	10 mL (< 25 μL)	HDPE, EO	FLL MLS				SLLG013SL	
	0.2	25	100 mL (< 100 μL)	HDPE, EO	FLL MLS			SLLG025SS		
					FLL MLL			SLFGR25LS		
					FLL MLS with Needle			SLFGL25BS		
								SLFGNR25VS		

Medical Applications*: CE marked and/or FDA registered for medical intended use.

Membrane	Pore Size (μm)	Diameter (mm)	Process Volume (hold-up)	Housing, sterilization method	Connections (inlet outlet)	CE	FDA (US)	25 PK	50 PK	100 PK	250 PK
PES Millipore Express® Plus Membrane <small>Fast flow and low binding</small>	0.22	25	100 mL (< 100 μL)	PVC, EO	FLL MLS	✓	✓	SLMP025SS			
					FLL MLL	✓	✓	SLMLP25SS			
		33	200 mL (< 100 μL)	Modified acrylic, RS	FLL MLS	✓		SLGP033RS	SLGP033RB		
	0.45	33	200 mL (< 100 μL)	Modified acrylic, RS	FLL MLS	✓	✓	SLHP033RS	SLHP033RB		
PVDF Durapore® Membrane <small>Lowest protein binding</small>	0.22	33	100 mL (< 100 μL)	Modified acrylic, RS	FLL MLS	✓		SLVV033RS			
		13	10 mL (< 25 μL)	HDPE, EO	FLL MLS	✓	✓	SLVVM33RS			
		25	100 mL (< 100 μL)	PVC, EO	Vented FLL MLS	✓	✓	SLGVV255F			
					Vented FLL MLL	✓	✓	SLGV0250S			
	0.45	33	100 mL (< 100 μL)	Modified acrylic, RS	FLL MLS	✓		SLGV033RS	SLGV033RB		
		13	10 mL (< 25 μL)	HDPE, EO	FLL MLS	✓	✓	SLGV033RS	SLGV033RB		
		25	100 mL (< 100 μL)	PVC, EO	FLL MLS	✓	✓	SLHV013SL			
		33	100 mL (< 100 μL)	Modified acrylic, RS	FLL MLS	✓	✓	SLHV033RS	SLHV033RB		
PVDF Durapel™ Membrane <small>Superhydrophobic for vial venting and transducer protection</small>	0.22	25	N/A	PVC, EO	FLL Vial Spike	✓		SLGV25LS			
MCE MF-Millipore™ Membrane <small>Most referenced general purpose membrane</small>	0.22	25	100 mL (< 100 μL)	PVC, EO	FLS MLS	✓	✓	SLGV25XS			
					FLL MLS	✓	✓	SLGV25PS			
		33	100 mL (< 100 μL)	Modified acrylic, EO	FLL MLS	✓	✓	SLGV025US			
	0.45	33	100 mL (< 100 μL)	Modified acrylic, EO	FLL MLS	✓	✓	Vented FLL MLS	SLGS033SS	SLGS033SB	
PTFE Fluoropore™ Membrane <small>Hydrophobic for venting and gas filtration</small>	0.22	25	100 mL (< 100 μL)	PVC, EO	FLL MLL	✓	✓	SLGL0250S	SLGS033SS	SLGS033SB	
						✓	✓	SLGSM33SS			
		33	100 mL (< 100 μL)	Modified acrylic, EO	FLL MLS	✓	✓	SLHA033SS	SLHA033SB		
	0.45	33	100 mL (< 100 μL)	Modified acrylic, EO	FLL MLS	✓	✓	SLHAM33SS			
PTFE Fluoropore™ Membrane <small>Hydrophobic for venting and gas filtration</small>	0.8	25	100 mL (< 100 μL)	PVC, EO	Vented FLL MLS	✓	✓	SLAAV255F			
	0.8	33	100 mL (< 100 μL)	Modified acrylic, EO	FLL MLS	✓	✓	SLAA033SS	SLAA033SB		
						✓	✓	SLAM33SS			
					FLL MLS	✓	✓	SLFG025LS			
					FLL MLS with Needle	✓		SLFGN25VS			

*Medical devices are only sold in countries where they are registered. Please contact your local customer support team for availability.

Venting and Gas Filtration:

Autoclavable for sterile-filtering gases / Venting sterile containers / In-line vacuum pump protection

Membrane	Pore size (μm)	Diameter (mm)	Housing and Sterilization method	Inlet connection	Outlet connection	10 PK	25 PK	50 PK	100 PK
PTFE Fluoropore™ Membrane	0.20 μm	25 mm	PP, Autoclavable	FLL	MLS			SLFG02550	
Hydrophobic chemistry for gas filtration	0.20 μm	50 mm	PP, Autoclavable	HB	HB	SLFG05010			
					1/8 in. NPTM	SLFG55010			
				HB (latex)	1/8 in. NPTM	SLFG65010			SLFG65000
				1/8 in. NPTM	1/8 in. NPTM	SLFG75010			SLFG75000
0.45 μm	50 mm	PP, Autoclavable	HB (silicone)	HB (silicone)	HB (silicone)	SLFG85010			SLFG85000
					HB	SLFH05010			SLFH05000

Non-Sterile Millex® syringe filters you can trust.



Chromatography

HPLC, IC, GC / General particle removal / Industrial / Environmental

Membrane	Diameter (mm)	Pore Size (μm)	Process Volume (hold-up)	50 units/pk	100 units/pk	250 units/pk	1000 units/pk
PTFE Hydrophilic Millipore® LCR Membrane	4	0.20	1 mL (< 10 μL)	SLLGR04NL			
		0.45	1 mL (< 10 μL)	SLLHR04NL			
Lowest extractables and excellent solvent resistance	13	0.20	10 mL ($\leq 15 \mu\text{L}$)	SLLGX13NL			SLLGX13NK
		0.45	10 mL ($\leq 15 \mu\text{L}$)	SLCRX13NL SLCRX13TL*			SLCRX13NK
	33	0.20	100 mL ($\leq 80 \mu\text{L}$)	SLLG033NS		SLLG033NB	SLLG033NK
		0.45	100 mL ($\leq 80 \mu\text{L}$)	SLCR033NS		SLCR033NB	SLCR033NK
PTFE Hydrophilic IC Millex® Filters	13	0.20	10 mL ($\leq 25 \mu\text{L}$)	SLLGC13NL			
		0.45	10 mL ($\leq 25 \mu\text{L}$)	SLLHC13NL			
Low IC extractables/Ion Chromatography Certified	25	0.20	100 mL ($\leq 100 \mu\text{L}$)	SLLGC25NS			
		0.45	100 mL ($\leq 100 \mu\text{L}$)	SLLHC25NS			
PTFE Hydrophobic Fluoropore™ Membrane	4	0.20	1 mL (< 10 μL)	SLFGR04NL			
		0.45	1 mL (< 10 μL)	SLFHR04NL			
Excellent solvent resistance	13	0.20	10 mL ($\leq 15 \mu\text{L}$)	SLFGX13NL SLFGX13TL*			SLFGX13NK
		0.45	10 mL ($\leq 15 \mu\text{L}$)	SLFHX13NL SLFHX13TL*			SLFHX13NK
	33	0.20	100 mL ($\leq 80 \mu\text{L}$)	SLFG033NS		SLFG033NB	SLFG033NK
		0.45	100 mL ($\leq 80 \mu\text{L}$)	SLFH033NS		SLFH033NB	SLFH033NK
PVDF Durapore® Membrane	4	0.22	1 mL (< 10 μL)	SLGVR04NL			SLGVR04NK
Low-protein binding		0.45	1 mL (< 10 μL)	SLHVR04NL			SLHVR04NK
	13	0.22	10 mL ($\leq 15 \mu\text{L}$)	SLGVX13NL SLGVX13TL*			SLGVX13NK
		0.45	10 mL ($\leq 15 \mu\text{L}$)	SLHVX13NL SLHVX13TL*			SLHVX13NK
	33	0.22	100 mL ($\leq 80 \mu\text{L}$)	SLGV033NS		SLGV033NB	SLGV033NK
		0.45	100 mL ($\leq 80 \mu\text{L}$)	SLHV033NS		SLHV033NB	SLHV033NK
Nylon Membrane	13	0.20	10 mL ($\leq 15 \mu\text{L}$)	SLGNX13NL SLGNX13TL*			SLGNX13NK
Broad chemical compatibility		0.45	10 mL ($\leq 15 \mu\text{L}$)	SLHNX13NL SLHNX13TL*			SLHNX13NK
	33	0.20	100 mL ($\leq 80 \mu\text{L}$)	SLGN033NS		SLGN033NB	SLGN033NK
		0.45	100 mL ($\leq 80 \mu\text{L}$)	SLHN033NS		SLHN033NB	SLHN033NK
PES Millipore Express® Membrane	13	0.22	10 mL ($\leq 15 \mu\text{L}$)	SLGPX13NL			SLGPX13NK
		0.45	10 mL ($\leq 15 \mu\text{L}$)	SLHPX13NL			SLHPX13NK
Fastest flow, high throughput	33	0.22	100 mL ($\leq 80 \mu\text{L}$)	SLGP033NS		SLGP033NB	SLGP033NK
		0.45	100 mL ($\leq 80 \mu\text{L}$)	SLHP033NS		SLHP033NB	SLHP033NK
MCE		0.22	100 mL ($\leq 100 \mu\text{L}$)			SLGS025NB†	
General laboratory filtration of aqueous solutions	25	0.45	100 mL ($\leq 100 \mu\text{L}$)			SLHA025NB†	SLHA025NK†
		0.8	100 mL ($\leq 100 \mu\text{L}$)			SLAA025NB†	SLAA025NK†

† PVC Housing

Automation Compatible

Dissolution testing / HPLC sample prep

Membrane	Diameter (mm)	Pore Size (μm)	Process Volume (hold-up)	200 (8 x 25) units/pk	1000 units/pk
Durapore® Membrane (PVDF)	25	0.45	100 mL ($\leq 100 \mu\text{L}$)	SLHVDZ5NZ	SLHVDZ5NK
Millipore® LCR Membrane (Hydrophilic PTFE)	25	0.20	100 mL ($\leq 100 \mu\text{L}$)	SLLGDZ5NZ	SLLGDZ5NK
		0.45	100 mL ($\leq 100 \mu\text{L}$)	SLCRDZ5NZ	SLCRDZ5NK
Nylon Membrane	25	0.20	100 mL ($\leq 100 \mu\text{L}$)	SLGNDZ5NZ	SLGNDZ5NK
		0.45	100 mL ($\leq 100 \mu\text{L}$)	SLHNDZ5NZ	SLHNDZ5NK
Glass Fiber Filter	25	1.0	100 mL ($\leq 250 \mu\text{L}$)	SLPBDZ5NZ	SLPBDZ5NK
Durapore® Membrane (PVDF) with glass fiber prefilter	25	0.45	100 mL ($\leq 250 \mu\text{L}$)	SLHVBZ5NZ	SLHVBZ5NK
Millipore® LCR Membrane (Hydrophilic PTFE) with glass fiber prefilter	25	0.45	100 mL ($\leq 250 \mu\text{L}$)	SLCRBZ5NZ	SLCRBZ5NK
Nylon Membrane with glass fiber prefilter	25	0.45	100 mL ($\leq 250 \mu\text{L}$)	SLHNBZ5NZ	SLHNBZ5NK

High Particulate Filtration & Automation Compatible

Chromatography sample preparation / Wine analysis / General particulate removal / Industrial / Environmental

Membrane	Diameter (mm)	Pore Size (μm)	Process Volume (hold-up)	50 units/pk	200 (8 x 25) units/pk	1000 units/pk
Millipore® LCR (Hydrophilic PTFE) with graduated multi-layer glass fiber prefilter	25	0.20	100 mL (< 250 μL)	SLLGM25NS		SLLGM25NK
		0.45	100 mL (< 250 μL)	SLCRM25NS		SLCRM25NK
Durapore® (PVDF) with graduated multi-layer glass fiber prefilter	25	0.45	100 mL (< 250 μL)	SLHVM25NS	SLHVMZ5NZ	SLHVM25NK
Nylon Membrane with graduated multi-layer glass fiber prefilter	25	0.20	100 mL (< 250 μL)	SLGNM25NS		SLGNM25NK
		0.45	100 mL (< 250 μL)	SLHNM25NS	SLHNMZ5NZ	SLHNM25NK

Housing Materials (non-sterile)

Application	4 mm	13 mm	25 mm	33 mm	Millex Samplicity® Filters
Chromatography, automation, high-particulate filtration	High density polyethylene	Polypropylene	High density polyethylene	Polypropylene	Polypropylene

Inlet Fittings: Female Luer-Lok™ Outlet Fittings: Male Luer Slip, Male Stepped (4 mm filters), and *Tube outlet where noted.

Samplicity® G2 Filtration System for HPLC Samples (The better way to use Millex® Filters)

A vacuum filtration system that allows simultaneous filtration of multiple samples (1-8) directly into standard sized HPLC, UPLC, GC, sample vials (12 x 32 mm). The Samplicity® G2 filtration system is a faster and easier way to use Millex® 33 mm syringe filters when filtering multiple samples.

Samplicity® System and Accessories

Samplicity® G2 System	SAMP2SYSB
Vial Trays	SAMVIALTR
Waste Trays	SAMWASTTR
Tube Set Assembly	SAMTUBING
Replacement Lid	SAMP2LID

Millex® Filters for the Samplicity® G2 System

Membrane	Pore Size (μm)	250 units/pk	1000 units/pk
Hydrophilic PTFE	0.20	SAMP2LGNB	SAMP2LGNK
	0.45	SAMP2LCRB	SAMP2LCRK
Durapore® Membrane (PVDF)	0.22	SAMP2GVNB	SAMP2GVNK
	0.45	SAMP2HVNBNB	SAMP2HVNPK
Nylon	0.20	SAMP2GNNB	SAMP2GNPK
	0.45	SAMP2HNNB	SAMP2HNNPK
PES	0.22	SAMP2GPBNB	SAMP2GPNP
	0.45	SAMP2HPNB	SAMP2HPNK

Millex Samplicity® Filters

Membrane	Pore Size (μm)	96 units/pk	384 units/pk
Hydrophilic PTFE	0.20	SAMPLG001	SAMPLG004
	0.45	SAMPLCR01	SAMPLCR04



To learn more, please visit: SigmaAldrich.com/OneMillex